

## 20LT SPRING GEAR OIL PUMP

Model No.	Description
SP65160	<p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>• Pump type: Spring operated pump</li> <li>• Flow: 300 ml / stroke</li> <li>• Suction tube length: 325mm for 20Ltr Drum</li> </ul> <p><b>Features:</b></p> <ul style="list-style-type: none"> <li>• Designed to fit a 20L drum and is ideal for transferring non-corrosive fluids of medium to heavy viscosity, such as engine oil, gear oil, transmission fluid, automotive additives, machine oil and lubricant</li> <li>• Spring operated pump and unique swivelling pump head assembly allows the hose to follow the operator</li> </ul> <ul style="list-style-type: none"> <li>• Inlet: 45mm O.D.</li> <li>• Outlet: 17mm O.D with 1370mmL PVC hose &amp; controllable oil gun</li> <li>• Max. viscosity: 5,000 SSU</li> <li>• Gun holder to ensure the extra oil flows back into the pail to prevent spills and accidents</li> <li>• Robust zinc pump head and steel pump body assembly ensure long working life</li> </ul>



## 60LT SPRING GEAR OIL PUMP

Model No.	Description
SP65162	<p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>• Pump type: Spring operated pump swivelling pump head</li> <li>• Flow: 500 ml / stroke</li> <li>• Suction tube length: 535mm for 60Ltr drum</li> <li>• Inlet: 48mm O.D.</li> </ul> <p><b>Features:</b></p> <ul style="list-style-type: none"> <li>• Designed to fit a 60L drum and is ideal fo transferring non-corrosive fluids of medium to heavy viscosity, such as engine oil, gear oil, transmission fluid, automotive additives, machine oil and lubricant</li> <li>• Spring operated pump and unique swivelling pump head assembly allows the hose to follow the operator</li> </ul> <ul style="list-style-type: none"> <li>• Outlet: 17mm O.D with 1370mmL PVC hose &amp; controllable oil gun.</li> <li>• Wetted parts: Steel, Zinc, PE, PVC &amp; NBR</li> <li>• Max. fluid temperature: 140°F / 60°C</li> <li>• Max. viscosity: 5,000 SSU</li> <li>• Gun holder to ensure the extra oil flows back into the pail to prevent spills and accidents</li> <li>• Robust zinc pump head and steel pump body assembly ensure long working life</li> <li>• Supplied with suction filter to sift the dirt and extend pump life</li> </ul>



## LEVER ACTION 200LT DRUM PUMP

Model No.	Description
SP65170	<p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>• Flow: 400ml per stroke</li> <li>• Mounting: 2 inch MNPT bung adapter</li> <li>• Inlet: 7/8 inch O.D.</li> </ul> <p><b>Features:</b></p> <ul style="list-style-type: none"> <li>• Used for dispensing or transferring non-corrosive and petroleum based fluids, such as diesel, kerosene, transmission fluid, machine oil, lube oil, fuel oil, anti-freeze, etc.</li> </ul> <ul style="list-style-type: none"> <li>• Outlet: 3/4 inch height-angle &amp; normal curved</li> <li>• Maximum fluid viscosity: 4000 SSU</li> <li>• Ideal for heavy-duty use in industrial, automotive and agricultural applications</li> <li>• Self-priming unit</li> <li>• Do not use with organic solvents, alkalis, acids &amp; water-based fluids</li> </ul>



## ROTARY GEARED 200LT DRUM PUMP

Model No.	Description
SP65175	<p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>• Flow: 1L / stroke</li> <li>• Mounting: 2" MNPT bung adapter</li> <li>• Inlet: 1-1/4" O.D.</li> </ul> <p><b>Features:</b></p> <ul style="list-style-type: none"> <li>• Used for dispensing or transferring low viscosity and non-corrosive petroleum based fluids, such as petrol, diesel, kerosene, lube, fuel, machine oil, etc.</li> <li>• Supplied with 2" bung adapter, a rubber delivery hose and non-drip nozzle</li> </ul> <ul style="list-style-type: none"> <li>• Outlet: 1" O.D. curved spout</li> <li>• Maximum fluid viscosity: 500 SS or SAE 30</li> <li>• Self-priming unit, dispenses approximately 1 litre per stroke</li> <li>• Do not use with organic solvents, alkalis, acids and water-based fluids</li> <li>• Supplied with suction filter to sift the dirt and extend pump life</li> </ul>

