

TYRE INFLATORS



PROFESSIONAL AIR INFLATOR WITH DEFLATOR

Model No.	Description
SP65500	<ul style="list-style-type: none"> • Highly accurate • Large and easy to read dial • Gauge fitted with heavy rubber bumper includes 600mm hose with clip-on chuck • Calibrated: 10-170 PSI in 2lb Increments 70-1200 kPa in 10 kPa increments • Gauge diameter: 80mm • Accuracy: <ul style="list-style-type: none"> +/- (F.S.x1%)+0.5 PSI at 2-100 PSI +/- (F.S.x2%)+0.5 PSI at 101-150 PSI • Pressure range: 2-150 PSI



PROFESSIONAL DIGITAL TYRE INFLATOR WITH DEFLATOR

Model No.	Description
SP65510	<ul style="list-style-type: none"> • Pressure measuring range: 0-160PSI (+/- 2% @25C) • Automatic shutoff after 60 seconds to conserve battery life • Dual chuck • Operating pressure: 90PSI • Air Flow: 1.2CFM at 100PSI

TYRE CHUCKS



DUAL TYRE CHUCK

Model No.	Description
SP65535	<ul style="list-style-type: none"> • Body: zinc/brass with rubber grip for comfort • 1/4" Female thread



AIR HOSE CHUCK, CLIP-ON STRAIGHT

Model No.	Description
SP65530	<ul style="list-style-type: none"> • Open 1/4 BSP • High quality solid brass clip-on air chuck



AIR HOSE CHUCK, ANGLE CLIP-ON

Model No.	Description
SP65531	<ul style="list-style-type: none"> • Open 1/4 BSP • High quality solid brass clip-on air chuck