

SP JETWASH

PRODUCT BULLETIN

PETROL PRESSURE WASHER

3000PSI - 11LPM

POWERED BY

HONDA

SPECIFICATIONS:

- Max Pressure: 3000psi/200bar
- Working Pressure: 2175psi
- Max Flow: 660 litres/hour (11 Litres/Minute)
- Engine: Honda GP160, (same specifications as a GX160 only made in Thailand - whilst the GP160 is made in China)
- Low oil shut down - Unit will shut down automatically, if the oil level gets low
- Low fuel consumption – allows you to do more work on one tank of fuel, saving you money
- Powerful and fuel efficient OHV, Overhead Valve 3.6KW 160cc engine

ENGINE SPECIFICATIONS:

MODEL	GP160
TYPE	4-stroke, overhead valve, single cylinder, horizontal shaft
BORE & STROKE	68 x 45 mm
DISPLACEMENT	163 cm ³
COMPRESSION RATIO	8.5:1
NET POWER	3.6kW (5.5HP) at 3,600 rpm
MAXIMUM NET TORQUE	10.3 Nm at 2,500 rpm
IGNITION SYSTEM	Transistorised magneto ignition
STARTING SYSTEM	Recoil
COOLING SYSTEM	Forced-Air
PTO SHAFT ROTATION	Counter-clockwise (from P.T.O. side)
FUEL CONSUMPTION AT RATED POWER	1.4 L/h at 3,600 rpm
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Splash
RECOMMENDED OIL	10W/30 API SG
OIL CAPACITY	0.6l
FUEL TANK CAPACITY	3.1l
DIMENSIONS	314 x 363 x 335mm
DRY WEIGHT	15.1kg



FEATURES:

SP300H

- Axial drive pump
- Sealed drive housing with Teflon coated drive shaft (maintenance free)
- Full brass head – high corrosion resistance
- Stainless steel pistons
- Thermal relief valve
- Detergent injector
- Adjustable pressure valve
- Rubber seals
- 8m steel braided hose
- 0°, 15°, 40° & Detergent Nozzles
- Full metal trigger valve and chrome steel lance
- Transparent Inlet water filter
- Solid rubber tyres
- 32mm steel tube frame – Strong and stable well balanced ergonomic frame with soft grip
- 24 months pump warranty
- 12 months Honda motor warranty

BARCODE: 9330514070048
 PACKAGE DIMENSIONS: 690(W) X 560(D) X 565(H)
 WEIGHT: 37.5KG

SPTOOLS.COM