GREASE GUNS

Pneumatic Single Shot Grease Gun

- · 40:1 ratio air motor
- · Heavy duty cast fiber composite body
- · 3-way loading: Bulk, filler pump or 450cc grease cartridge
 • Heavy duty super grip coupler
- for better grip
- · Non-Slip finish for better grip.
- · Air Inlet: 1/4"
- · Hose size: 3/8" I.D.
- · Weight: Only 1 Kg
- · 6" curved pipe with heavy duty coupler & 9" flexible hose with coupler



Pneumatic Single Shot Or Continuous Grease Gun

UNDER AIR INPUT PRESSURE: 60~120PSI

- Single Shot Mode: Max 4800PSI
 Continuous Mode: Max 2500PSI
- · Capacity: Cartridge-450cc, Bulk-500cc

CONTINUOUS MODE

· Greasing flow: Up to 150cc/min

FEATURES:

- 40:1 ratio air motor
- · Heavy duty cast aluminum body
- · 3-way loading: Bulk, filler pump or 450cc grease cartridge
- · Heavy duty super grip coupler for better grip & longer service life
- 6" curved pipe with coupler & 9" flexible hose with coupler



12" Grease Gun Flex Hose

- · Fits most grease gun accessories
- Working pressure: 4,500 PSI
- Burst pressure: 12.000 PSI
- 1/8" NPT
- · For hard to reach jobs
- For use with air & hand operated grease guns



18" Grease Gun Flex Hose

- · Fits most grease gun accessories
- Working pressure: 4,500 PSI
- Burst pressure: 12.000 PSI
- 1/8" NPT
- For hard to reach jobs
- For use with air & hand operated grease guns



High Pressure Lever Action Grease Gun

- · 3-way loading: Bulk, filler nipple or 450cc standard grease cartridge
- Working Pressure: 8000PSI
- Max Pressure: 10000 PSI



8pc Grease Gun Adapter Kit





Heavy Duty Coupler

- Three hardened jaws
- · 2" long coupler tapped for 1/8" pipe threads
- Recommended working pressure: 8000psi





Right Angle Coupler

- · Reach out-of-the-way zerk fittings such as those on ball joints
- Coupler fits standard grease guns: 1-5/8" long , 1/8" NPT





Mini-Grease Gun

- Chrome plated finish
- Working pressure 1000 PSI
- · Capacity bulk 80 cc
- · External taper degree: 50 degree / Caliber: 0.5mm







- · Bleeder valve for purging unwanted air use standard 450cc grease cartridge
- · Heavy duty super grip coupler, coupler includes ball check
- Non-slip finish for better grip
- Max pressure: 8000PSI



Double Action Fluid Transfer Pump

- · Perfect for transmissions, differentials, gear cases, lower units crankcases, etc.
- No priming necessary
- 39 Inch / 100cm flexible hose
- 500ml capacity

INCLUDES:

• 18" Nvlon Hose

• 4" Needle Nose Dispenser

Right Angle Grease Coupler

· Grease Injector Needle

· Seal-Off Dispenser

360° Swivel Coupler

· Grease Coupler

· Narrow Needle Nose Dispenser

- Two way vinyl hose for suction & discharge of fluids.
- Durable check valve
- · Heavy-duty aluminum container tube



Oil Suction Pump

- · Perfect for removing or replacing oil in: engines, transmissions, differentials, gearbox sumps & crankcases
- Enables easy access to awkward locations & ideal for vehicle & machinery use
- No priming necessary
- 10" Flexible hose
- 500ml capacity

